

products > > FANFARO ATF WS



## FANFARO ATF WS 8611

A special low-viscosity synthetic transmission fluid (ATF) for automatic gearboxes of TOYOTA/LEXUS vehicles with latest-generation TOYOTA and AISIN AW gearboxes, including sequential. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear of ball bearings, stuffing boxes and gears, a lasting service life of the whole transmission and fuel economy. It was developed on the basis of the requirements set by the company AISIN WARNER.

### Product properties:

- The highest-quality low-viscosity synthetic base with a consistent high viscosity index in a combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45°C) temperatures in winter and ensures a stable oil film under extreme loads and high temperatures in summer, ensures necessary antifriction properties even in the event of a discontinuity of the oil film during overloads;
- The high-technology combination of additives ensures good antifriction properties for gear couplings and required friction properties for friction elements thus ensuring a significant fuel economy, an exceptionally smooth transmission shift and a significant increase in the service life of all transmission elements. - It ensures a coordinated and smooth operation of clutches, extends the service life of friction elements, prevents hydraulic converter's contact elements from sliding when changing modes thus significantly reducing their wear;
- It has a superior thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits to a minimum, significantly increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;
- It protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;
- It effectively resists aeration and foam formation;
- It ensures a compatibility with all sealing materials, prevents them from swelling, hardening and shrinking that allows reducing the costs for spare parts and prevents leakages;
- It reduces noise.

It is recommended for last-generation Toyota and Aisin AW automatic gearboxes in which the compliance with the above-mentioned TOYOTA requirements is required, as well as for automatic gearboxes of passenger cars and commercial vehicles produced by European manufacturers.

Colour: red.

Comply with the manufacturer's instructions provided in the user's manual!

## **CORRESPONDS WITH REQUIREMENTS / SPECIFICATIONS / PRODUCTS:**

### **Specifications:**

### **Approval:**

### **Recommendation:**

AISIN WARNER AW-2

AISIN WARNER JWS 3309 ATF, ATF-0T4

FCA ATF+3

FCA ATF+4

GM 88863400

GM 88863401

LEXUS ATF WS Lifetime

LEXUS 08886-02303

LEXUS 08886-02305

LEXUS 08886-80803

LEXUS 08886-80807

LEXUS 08886-81210

MAN 339 Type Z1

TOYOTA ATF FZ

TOYOTA JWS 3324 ATF, ATF-0WS

TOYOTA JWS 3309, Type T-IV, 08886-81015

TOYOTA Type D-II

TOYOTA Type T

TOYOTA Type S-II

VOITH ATs 55.6335

FCA ACRC

LAND ROVER LR0022460

VOLKSWAGEN G 055 540-A2

JAMA JASO M315, Class 1-A- LV L A

AISIN WARNER JWS 3324 ATF, ATF-0WS

TOYOTA Type S-III

FCA ATF+2

FCA ATF+

FCA AB

FCA 8 & 9 Speed ATF, 68218925AA

FCA 236.10

FCA 236.12, 05127382AA

FCA 68333587AA

FCA SP-III

FCA Type 7176E

FCA Type 9602

ISUZU ATF WSI

ISUZU ATF II

ISUZU ATF-III

ISUZU Genuine ATF

**PACKAGES (ARTICLE NUMBER):**

FF8611-4