FANFARO COMRESSOR OIL ISO 150

2903

Highly-purified paraffin low-ash mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product properties:
- They contain antifriction, antiwear, anti-oxidising, anticorrosion and antifoaming additives;
- An excellent thermal stability;
- Great antiwear properties;
- An exceptional resistance to oxidisation and ageing;
- A minimal formation of deposits and sediments: it guarantees the cleanliness of all mechanical parts, prevents the risk of fire or explosion;
- It has excellent anticorrosion and antifoaming properties and a low evaporation capacity;
- They are recommended for use at ambient temperatures of -25 °C and up;
- They have excellent cooling properties;
- They are compatible with all sealing materials;
- The replacement period up to 4,000 running hours.

Use: all types of air piston-type (moderate and heavy operating modes) and air rotary (moderate operating mode) compressors with the outlet air temperature up to 220 °C. They are recommended for long life compressors.
It can be used in hydraulic systems as a low-ash oil.
In order to properly use them, thoroughly read the user's manual of the equipment.

CORRESPONDS WITH REQUIREMENTS / SPECIFICATIONS / PRODUCTS:

Specifications:
Approval:
Recommendation:
ISO Viscosity Grade 150
DIN 51506 (VBL)
DIN 51506 (VCL)
DIN 51506 (VDL)

ISO DP 6521 L-DAA
ISO DP 6521 L-DAB
ISO DP 6521 L-DAG
ISO DP 6521 L-DAH

PACKAGES (ARTICLE NUMBER):

208L (FF2903-DR)
20L (FF2903-20)